

373TMD Wamee Medical Grade Tablet

Slim, Rugged, Multi-functional Wireless Computing

The 373T/MD Rugged Medical Tablet features the integration of a brilliant 17" capacitive touch screen and a high performance, energy-efficient Intel® Pentium® Gold or Core™ i processor within a slim, durable package. With built-in front and back cameras, Wi-Fi as well as optional data capture modules, this medical tablet offers health professionals an effective tool to monitor, record and retrieve patient information. With its large, vivid display, the 373T/MD Rugged Medical Tablet shows a wide work area and detailed application interface to enhance user experience and workflow.


Features

- 17″ Full-HD capacitive touch screen, digital pen support
- Intel® Pentium® Gold or Core™ i processor
- Microsoft[®] Windows[®] 10/11 IoT Enterprise or Ubuntu operating system
- NIST compliant BIOS available
- ANSI/AAMI ES60601-1 certified with antimicrobial enclosure
- IP65-rated front panel
- Hot-Swappable battery pack
- Built-in front and back cameras

Major Options

- Smart card/CAC reader
- 4G LTE/AWS





Specifications

MODEL	316TMD		
SYSTEM			
CPU	Intel® Pentium® Gold 7505, Dual-Core, 3.5GHz (max turbo frequency) Intel® Core™ i5-1135G7, Quad-Core, 4.2GHz (max turbo frequency) Intel® Core™ i7-1165G7, Quad-Core, 4.7GHz (max turbo frequency)		
RAM	8GB to 16GB		
Storage	256GB to 1TB Flash		
Operating System	Microsoft® Windows® 10 /11 IoT Enterprise or Ubuntu		
NIST Compliance	NIST compliant BIOS available		
Display	17" capacitive touch screen		
Display Resolution	1920 x 1080		
Control Switch and Buttons	1 power button, 3 programmable buttons		
Speaker Microphone	Built-in speaker and microphone		
Camera	Full-HD front camera and 8MP back camera		
NETWORK INTERFACE			
WLAN	Wi-Fi 802.11ax, 2.4GHz/ 5GHz dual band		
I/O PORTS			
USB Ports	6 x USB 3.0 x 6, 1 x USB Type C		
Headset Jack	1(3.5mm)		
Ethernet Port	1		
DC-in	1		
MECHANICAL AND ENVIRONMENTAL			
AC/DC Adapter	Input: 100-240V AC; Output: 18.5V DC, 3.89A		
Battery Pack	Hot swappable battery, 11.4V, 5400mAh		
Enclosure	ABS + PC plastics and magnesium-aluminum alloy; antimicrobial enclosure		
Dimensions (H x W x D)	16.9 x 11.1 x 1.06 in/430 x 282 x 27 mm		
Weight	4.41 lbs/ 2 kg		
VESA Complient Mounting	75 x 75 VESA Stndard		
Durability	IP65 rated front panel		
Regulatory	FCC/IC, CE/CB, RCM, CCC, ANSI/AAMI ES60601-1		
Temperature	Operation: -10°C to 60°C (-14°F to 140°F), optional -30°C to 60°C (-22°F to 140°F) Storage: -55°C to 70°C (-67°F to 158°F)		
Humidity	0% – 90% non-condensing		
MAJOR OPTIONS			
Mobile Broadband	4G LTE/AWS		
Smart Card/CAC Reader	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card		





Accessories

The 373T MD Tablet has customized accessories to meet numerous deployment needs.

DIGITAL I	PEN	/
Pen Tip	Diameter: 0.059 in/ 1.5mm, replaceable	

WALL/ VEHICLE MOUNT CRADLE

Secure Tablet mounting and charging with power, Ethernet pass-through, HDMI-out, COM, and USB ports



BATTERY CHARGING KITS

BATTERY PACK



3-SLOT BATTERY HOLSTER



